

CONVERTAPIPE® (BLACK COVER)

Convertapipe® is a flexible rubber hose used for process piping in suction or discharge service. It is frequently used for handling ore in water suspension, dry or water suspended grain, chemicals, metal shavings, wood particles, fish, shells and some sand and gravel. Rated at full vacuum, Convertapipe® features a black SBR/EPDM cover that is resistant to snagging, abrasion and weather aging. It is available in a variety of tube gauges, compounds and end types.



RESISTANCE 
BRANDING Thermoid HBD Industries
 Convertapipe WP
 Made In USA

Cover Color: Black
Oil Resistance: Limited
Construction:
Tube: SBR/NR
Cover: SBR/EPDM
Cover Thickness: 25 lb. WP and 50 lb. WP - 3/64"
 75 lb. through 250 lb. - 1/16"
 For other thicknesses, contact Salisbury for details
Reinforcement: Square woven fabric plies with helical wire(s) embedded in a cushion of rubber
Temperature Range: -40°F to +160°F
 -40°C to +71°C
Packaging: Make to Order (MTO), minimum order \$250.00
 Contact Salisbury for details
Type Ends:
 1. Straight 4. Flexseal™
 2. Enlarged 5. Built-In Nipple
 3. Flexlock™ 6. Soft Cuffs

1/4" Tube	Nominal I.D.		Nominal O.D.		Fits Over Pipe I.D.		Type Ends	Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)	(inches)	(mm)		(inches)	(mm)	(lb/ft)	(Kg/m)
1	25.40	1.94	49.21				1 2	25	0.17	1.20	1.79
1-1/2	38.10	2.44	61.91				1 2 3	25	0.17	1.70	2.53
2	50.80	3.00	76.20				1 2 3 5	25	0.17	2.70	4.02
2-3/8	60.33	3.38	85.73	2	50.80		1	25	0.17	2.70	4.02
2-1/2	63.50	3.50	88.90				1 2 3 5	25	0.17	2.80	4.17
2-7/8	73.03	3.88	98.43	2-1/2	63.50		1	25	0.17	3.20	4.76
3	76.20	4.06	103.19				1 2 3 5	25	0.17	3.70	5.51
3-1/2	88.90	4.56	115.89	3	76.20		1 2 3 5	25	0.17	4.10	6.10
4	101.60	5.06	128.59				1 2 3 5	25	0.17	5.00	7.44
4-1/2	114.30	5.56	141.29	4	101.60		1	25	0.17	5.50	8.18
5	127.00	6.25	158.75				1 2 3 5	25	0.17	6.10	9.08
6	152.40	7.31	185.74				1 2 3 5	25	0.17	8.10	12.05
6-5/8	168.28	7.94	201.61	6	152.40		1	25	0.17	8.60	12.80
8	203.20	9.44	239.71				1 2 3 5	25	0.17	10.80	16.07
8-5/8	219.08	10.06	255.59	8	203.20		1	25	0.17	11.80	17.56
10	254.00	11.50	292.10				1 2 3 5	25	0.17	14.60	21.72
10-3/4	273.05	12.25	311.15	10	254.00		1	25	0.17	16.90	25.15
12	304.80	13.56	344.49				1 2 3 5	25	0.17	18.20	27.08
12-3/4	323.85	14.31	363.54	12	304.80		1	25	0.17	21.00	31.25
14	355.60	15.81	401.64	14" OD	355.60		1 3 5	25	0.17	25.10	37.35
16	406.40	17.81	458.79	16" OD	406.40		1 3 5	25	0.17	31.80	47.31

MATERIAL HANDLING