

TRANSPORTER® EBONITE™ CORRUGATED TANK TRUCK

The Transporter® Ebonite™ Corrugated Tank Truck is recommended for hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. It features a flat corrugated NBR/PVC cover which is ideal for those applications where flexibility is important. The reinforcement of two plies of polyester cord with a dual wire helix enables this hose to be rated at full vacuum and provides a constant working pressure of 150 psi, regardless of hose size.



RESISTANCE    
BRANDING Thermoid HBD Industries Inc.
 Ebonite™ 150 PSI WP
 Made In USA

Cover Color: Black
Oil Resistance: High
Construction:
Tube: NBR, RMA Class A
Cover: NBR/PVC corrugated, RMA Class B
Reinforcement: 2 plies of polyester cord with a dual wire helix(es) between plies
Temperature Range: -30°F to +200°F
 -34°C to +93°C
Packaging: 100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17813045002▲	1	25.40	1.53	38.89	2	150	1.03	2.00	50.80	0.60	0.89
17813046002▲	1-1/4	31.75	1.78	45.24	2	150	1.03	2.50	63.50	0.70	1.04
17813047002	1-1/2	38.10	2.06	52.39	2	150	1.03	3.00	76.20	0.90	1.34
17813048002	2	50.80	2.56	65.09	2	150	1.03	4.50	114.30	1.20	1.79
17813050002	3	76.20	3.56	90.49	2	150	1.03	6.00	152.40	1.80	2.68
17813055002	4	101.60	4.66	118.27	2	150	1.03	8.00	203.20	2.70	4.02

Petroleum

PETROLEUM/LPG

Consult coupling manufacturers for specific coupling recommendations/attachment procedures.